

Laboratory shakers





Advantages

- orbital movement
- microprocessor control of rotation and time
- orbital diameter: 10...25mm
- max shaking weight: 10kg
- variable speed control: 10...300 rpm
- shaking mode: from 1min to 99h, or continuous
- LED digital display
- anti-skid mat (option)
- various shaking tables
- can be located inside cooled incubators


WL 280


Accessories

- anti-skid mat
- universal shaking table
- separating funnel attachment
- fixing clip support
- dish attachment
- test tube support
- Erlenmeyer flasks (25...2000 ml) attachment

| Model | | WL 280 | WL 350 | WL 500 | WL 700 |
|---|--------|---|---|---|---|
| Parameter | |  |  |  |  |
| movement | | orbital, horizontal | | | |
| controller | | microprocessor | | | |
| display | | LCD display | | | |
| speed range [rpm] | | 10...300 | | 10...300 | 10...100 |
| accuracy [rpm] | | 10 | | | |
| amplitude [mm] | | 10 | 10 or 20 | 10 or 20 | 25 |
| max load capacity [kg] | | 10 | | | |
| shaking mode | | 1min...99h or continuous | | | |
| dimensions without / with shaking table [mm] | width | 320 | 390 | 550 | 700 |
| | height | 120 / 220 | 120 / 220 | 120 / 220 | 120 / 220 |
| | depth | 330 | 400 | 440 | 420 |
| nominal power [W] | | 60 | 60 | 60 | 60 |
| weight with shaking table [kg] | | 13 | 15 | 22 | 25 |
| ambient temperature [°C] | | +10...+40 | | | |
| humidity [%] | | up to 70 | | | |
| voltage 50 Hz [V] | | 220...240 | | | |
| warranty | | 24 months | | | |
| manufacturer | | POL-EKO-APARATURA | | | |